

TRURAN MACHINERY

APL-300

高精度小尺寸自動裁斷機

High-accuracy Mini-sized Automatic Cutting Machine



APL-300

▶ 優越且安定的下死點精度 Well-designed and Stabilized Bottom Dead-point Accuracy

- ◆ 機台結構經特殊設計及基本工法加工, 裁斷精度穩定性極高
- Specially designed machine structure and basic machining method, which provides extremely high cutting accuracy and stability.

▶ 親和的操作介面 User Friendly Operation Interface

- ◆ 數位化的參數設定, 方便SOP的管理, 省去冗長的教育訓練時間
- Digitalized parameter setting to facilitate the SOP management, while saving lengthy education and training time.

▶ 自動潤滑系統 Automatic Lubrication System

- ◆ 本機配有自動潤滑系統, 可簡化日常保養之流程
- With Automatic Lubrication System, it simplifies the procedure of daily maintenance.

▶ 裁斷深度調整機構 Cutting Depth Adjusting Mechanism

- ◆ 調整深度完全數位化, 調整簡便快速
- Totally digitalized depth adjustment in achieving convenient and fast adjusting.

▶ 全斷及半斷加工 Full-cut and Semi-cut Machining Effect

- ◆ 裁斷深度最小可調整至0.003mm, 精度高可輕易做全斷及半斷加工
- The cutting depth can be adjusted to the minimal 0.003mm in providing high accuracy for easier full-cut and semi-cut machining effect.

▶ 二次加工對應 Secondary Machining Flexibility

- ◆ 可對應作雙站對位裁斷加工
- It is flexible for carrying out inter-station alignment cutting.

▶ 鋼模裁斷對應 Steel Form Cutting Flexibility

- ◆ 可支援鋼模沖孔裁斷加工
- It supports steel form punching and cutting.

▶ 適用材料 Applicable Materials

- ◆ 各種光學膜, PET, 光學膠, 一般膠帶, 遮光用材料, 泡棉...等
- All photoelectric films, PET, photoelectric gels, general adhesive tapes, light-shielding materials, and foam, etc.

▶ 機械規格 Mechanical Specifications

有效面積 Effective Area Size	300mm x 300mm
下死點精度 Bottom Dead-Point Accuracy	+/-0.005mm
裁斷效率 Cutting Efficiency	180次/min (標準型 standard model)
電壓 Voltage	220V 50Hz 3P
機械尺寸 Machine Measurement	W1600mm x L1250mm x H2200mm
機械重量 Machine Weight	2500kg



本公司通過 ISO 9001 國際認證
As function ISC concept

■ 特殊機種歡迎訂購
WELCOME CUSTOM-MADE ORDERS FOR SPECIAL REQUEST.

■ 本公司不斷在機械品質和性能上求精進, 若有設計變更不再另行通知。
We reserve the right to modify the specifications relating to any of the above listed machines without notice.